


Performance

Metrics

First Contentful Paint	1.7 s	Time to Interactive	3.9 s
Speed Index	2.6 s	Total Blocking Time	0 ms
▲ Largest Contentful Paint	6.1 s	Cumulative Layout Shift	0

Values are estimated and may vary. The [performance score is calculated](#) directly from these metrics. [See calculator](#).

View Original Trace



Opportunities — These suggestions can help your page load faster. They don't [directly affect](#) the performance score.

Opportunity	Estimated Savings
<div>▲ Eliminate render-blocking resources</div> <div>Resources are blocking the first paint of your page. Consider delivering critical JS/CSS inline and deferring all non-critical JS/styles. Learn more.</div> <div><div><input checked="" type="checkbox"/> Show 3rd-party resources (1)</div></div>	0.89 s
URL	Transfer sizePotential savings
...serve/13 (landingpage.saltcorn.com)	20.5 KiB300 ms
...css/fontawesome.min.css (cdnjs.cloudflare.com)	10.8 KiB930 ms

URL	Cache TTL	Transfer size
/saltcorn.js (landingpage.saltcorn.com)	15 m	4 KiB
/saltcorn.css (landingpage.saltcorn.com)	15 m	2 KiB
...serve/1 (landingpage.saltcorn.com)	1 h	416 KiB
...serve/13 (landingpage.saltcorn.com)	1 h	21 KiB
...serve/9 (landingpage.saltcorn.com)	1 h	18 KiB
...serve/8 (landingpage.saltcorn.com)	1 h	12 KiB
...serve/5 (landingpage.saltcorn.com)	1 h	12 KiB

Avoid chaining critical requests — 7 chains found ^

The critical request chains below show you what resources are loaded with a high priority. Consider reducing the length of chains, reducing the download size of resources or deferring the download of unnecessary resources to improve page load. [Learn more](#).

Maximum critical path latency: **1,040 ms**

Initial Navigation

https://landingpage.saltcorn.com

...serve/13 (landingpage.saltcorn.com) - **130 ms, 20.51 KiB**
 ...css/fontawesome.min.css (cdnjs.cloudflare.com) - **60 ms, 10.79 KiB**
 /saltcorn.css (landingpage.saltcorn.com) - **60 ms, 1.87 KiB**
 /jquery-3.6.0.min.js (code.jquery.com) - **80 ms, 30.40 KiB**
 ...umd/popper.min.js (cdnjs.cloudflare.com) - **50 ms, 7.04 KiB**
 ...js/bootstrap.min.js (stackpath.bootstrapcdn.com) - **100 ms, 14.67 KiB**
 /saltcorn.js (landingpage.saltcorn.com) - **40 ms, 4.09 KiB**

Keep request counts low and transfer sizes small — 13 requests • 905 KiB ^

To set budgets for the quantity and size of page resources, add a budget.json file. [Learn more](#).

Resource type	Requests	Transfer size
Total	13	904.6 KiB
Image	4	458.0 KiB
Script	5	410.8 KiB
Stylesheet	3	33.2 KiB
Document	1	2.7 KiB
Media	0	0.0 KiB
Font	0	0.0 KiB
Other	0	0.0 KiB
Third-party	5	417.5 KiB



Largest contentful paint element — 1 element found

This is the largest contentful element painted within the viewport. [Learn more](#)

Element



section.page-section.pt-2

Avoid long main-thread tasks — 1 long task found



Lists the longest tasks on the main thread –useful for identifying worst contributors to input delay. [Learn more](#)

☒ Show 3rd-party resources (1)

URL	Start Time	Duration
...js/bootstrap.min.js (stackpath.bootstrapcdn.com)	6,069 ms	51 ms

Passed audits (27)



Properly size images



Serve images that are appropriately-sized to save mobile data and improve load time. [Learn more](#).

Defer off-screen images



Consider lazy loading offscreen and hidden images after all critical resources have finished loading to lower time to interactive. [Learn more](#).

Minify CSS



Minifying CSS files can reduce network payload sizes. [Learn more](#).

Minify JavaScript



Minifying JavaScript files can reduce payload sizes and script parse time. [Learn more](#).

Efficiently encode images



Optimised images load faster and consume less mobile data. [Learn more](#).

Serve images in next-gen formats



Image formats like JPEG 2000, JPEG XR and WebP often provide better compression than PNG or JPEG, which means faster downloads and less data consumption. [Learn more](#).

Enable text compression



Text-based resources should be served with compression (gzip, deflate or brotli) to minimise total network bytes. [Learn more](#).

Pre-connect to required origins



Consider adding `preconnect` or `dns-prefetch` resource hints to establish early connections to important third-party origins. [Learn more.](#)

Avoid multiple page redirects ^

Redirects introduce additional delays before the page can be loaded. [Learn more.](#)

Pre-load key requests ^

Consider using `<link rel=preload>` to prioritise fetching resources that are currently requested later in page load. [Learn more.](#)

Use HTTP/2 ^

HTTP/2 offers many benefits over HTTP/1.1, including binary headers, multiplexing and server push. [Learn more.](#)

Use video formats for animated content ^

Large GIFs are inefficient for delivering animated content. Consider using MPEG4/WebM videos for animations and PNG/WebP for static images instead of GIF to save network bytes. [Learn more](#)

Remove duplicate modules in JavaScript bundles ^

Remove large, duplicate JavaScript modules from bundles to reduce unnecessary bytes consumed by network activity.

Avoid serving legacy JavaScript to modern browsers ^

Polyfills and transforms enable legacy browsers to use new JavaScript features. However, many aren't necessary for modern browsers. For your bundled JavaScript, adopt a modern script deployment strategy using module/nomodule feature detection to reduce the amount of code delivered to modern browsers, while retaining support for legacy browsers. [Learn more](#)

Preload largest contentful paint image ^

Preload the image used by the LCP element in order to improve your LCP time. [Learn more.](#)

☐ Show 3rd-party resources (0)

URL	Potential savings
 ...serve/1 (landingpage.saltcorn.com)	0 ms

Avoids enormous network payloads — Total size was 905 KiB ^

Large network payloads cost users real money and are highly correlated with long load times. [Learn more.](#)

☒ Show 3rd-party resources (5)

URL	Transfer size
...serve/1 (landingpage.saltcorn.com)	416.2 KiB
...js/all.min.js (cdnjs.cloudflare.com)	354.6 KiB
/jquery-3.6.0.min.js (code.jquery.com)	30.4 KiB
...serve/13 (landingpage.saltcorn.com)	20.5 KiB
...serve/9 (landingpage.saltcorn.com)	17.8 KiB
...js/bootstrap.min.js (stackpath.bootstrapcdn.com)	14.7 KiB

URL	Transfer size
...serve/8 (landingpage.saltcorn.com)	12.3 KiB
...serve/5 (landingpage.saltcorn.com)	11.7 KiB
...css/fontawesome.min.css (cdnjs.cloudflare.com)	10.8 KiB
...umd/popper.min.js (cdnjs.cloudflare.com)	7.0 KiB

Avoids an excessive DOM size — 140 elements ^

A large DOM will increase memory usage, cause longer [style calculations](#) and produce costly [layout reflows](#). [Learn more](#).

Statistic	Element	Value
Total DOM Elements		140
Maximum DOM Depth	label	12
Maximum Child Elements	div.footer.text-left	14

User Timing marks and measures ^

Consider instrumenting your app with the User Timing API to measure your app's real-world performance during key user experiences. [Learn more](#).

JavaScript execution time — 0.0 s ^

Consider reducing the time spent parsing, compiling and executing JS. You may find delivering smaller JS payloads helps with this. [Learn more](#).

☐ Show 3rd-party resources (0)

URL	Total CPU Time	Script Evaluation	Script Parse
https://landingpage.saltcorn.com	106 ms	13 ms	6 ms
Unattributable	84 ms	3 ms	0 ms

Minimises main-thread work — 0.3 s ^

Consider reducing the time spent parsing, compiling and executing JS. You may find delivering smaller JS payloads helps with this. [Learn more](#)

Category	Time Spent
Other	122 ms
Script Evaluation	83 ms
Script Parsing & Compilation	36 ms
Parse HTML & CSS	29 ms
Style & Layout	28 ms
Rendering	10 ms
Garbage Collection	6 ms

All text remains visible during webfont loads



Leverage the font-display CSS feature to ensure text is user-visible while webfonts are loading. [Learn more.](#)

Minimise third-party usage — Third-party code blocked the main thread for 0 ms



Third-party code can significantly impact load performance. Limit the number of redundant third-party providers and try to load third-party code after your page has primarily finished loading. [Learn more.](#)

☐ Show 3rd-party resources (0)

Third-party	Transfer size	Main-Thread Blocking Time
Cloudflare CDN	372 KiB	0 ms
...js/all.min.js (cdnjs.cloudflare.com)	355 KiB	0 ms
jQuery CDN	30 KiB	0 ms
/jquery-3.6.0.min.js (code.jquery.com)	30 KiB	0 ms
Bootstrap CDN	15 KiB	0 ms
...js/bootstrap.min.js (stackpath.bootstrapcdn.com)	15 KiB	0 ms

Lazy load third-party resources with facades



Some third-party embeds can be lazy loaded. Consider replacing them with a facade until they are required. [Learn more.](#)

Avoid large layout shifts



These DOM elements contribute most to the CLS of the page.

Uses passive listeners to improve scrolling performance



Consider marking your touch and wheel event listeners as `passive` to improve your page's scroll performance. [Learn more.](#)

Avoids `document.write()`



For users on slow connections, external scripts dynamically injected via `document.write()` can delay page load by tens of seconds. [Learn more.](#)

Avoid non-composited animations



Animations which are not composited can be poor, slow and increase CLS. [Learn more](#)



Accessibility

These checks highlight opportunities to [improve the accessibility of your web app](#). Only a subset of accessibility issues can be automatically detected so manual testing is also encouraged.

Additional items to manually check (10) — These items address areas which an automated testing tool cannot cover. [Learn more in our guide on conducting an accessibility review.](#)



The page has a logical tab order

Tabbing through the page follows the visual layout. Users cannot focus elements that are offscreen. [Learn more.](#)

Interactive controls are keyboard focusable

Custom interactive controls are keyboard focusable and display a focus indicator. [Learn more.](#)

Interactive elements indicate their purpose and state

Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. [Learn more.](#)

The user's focus is directed to new content added to the page

If new content, such as a dialog, is added to the page, the user's focus is directed to it. [Learn more.](#)

User focus is not accidentally trapped in a region

A user can tab into and out of any control or region without accidentally trapping their focus. [Learn more.](#)

Custom controls have associated labels

Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. [Learn more.](#)

Custom controls have ARIA roles

Custom interactive controls have appropriate ARIA roles. [Learn more.](#)

Visual order on the page follows DOM order

DOM order matches the visual order, improving navigation for assistive technology. [Learn more.](#)

Offscreen content is hidden from assistive technology

Offscreen content is hidden with display: none or aria-hidden=true. [Learn more.](#)

HTML5 landmark elements are used to improve navigation

Landmark elements (<main>, <nav>, etc.) are used to improve the keyboard navigation of the page for assistive technology. [Learn more.](#)

Passed audits (18)**[aria-*] attributes match their roles**

Each ARIA `role` supports a specific subset of `aria-*` attributes. Mismatching these invalidates the `aria-*` attributes. [Learn more.](#)

[aria-hidden="true"] is not present on the document <body>

Assistive technologies, like screen readers, work inconsistently when `aria-hidden="true"` is set on the document `<body>`. [Learn more.](#)

[aria-*] attributes have valid values

Assistive technologies, such as screen readers, can't interpret ARIA attributes with invalid values. [Learn more.](#)

[aria-*] attributes are valid and not misspelled

Assistive technologies, such as screen readers, can't interpret ARIA attributes with invalid names. [Learn more.](#)

Buttons have an accessible name

When a button doesn't have an accessible name, screen readers announce it as 'button', making it unusable for users who rely on screen readers. [Learn more.](#)

The page contains a heading, skip link or landmark region

Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. [Learn more.](#)

Background and foreground colours have a sufficient contrast ratio

Low-contrast text is difficult or impossible for many users to read. [Learn more.](#)

Document has a `<title>` element

The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. [Learn more.](#)

ARIA IDs are unique

The value of an ARIA ID must be unique to prevent other instances from being overlooked by assistive technologies. [Learn more.](#)

Heading elements appear in a sequentially-descending order

Properly ordered headings that do not skip levels convey the semantic structure of the page, making it easier to navigate and understand when using assistive technologies. [Learn more.](#)

`<html>` element has a `[lang]` attribute

If a page doesn't specify a lang attribute, a screen reader assumes that the page is in the default language that the user chose when setting up the screen reader. If the page isn't actually in the default language, then the screen reader might not announce the page's text correctly. [Learn more.](#)

`<html>` element has a valid value for its `[lang]` attribute

Specifying a valid [BCP 47 language](#) helps screen readers announce text properly. [Learn more.](#)

Image elements have `[alt]` attributes

Informative elements should aim for short, descriptive alternative text. Decorative elements can be ignored with an empty alt attribute. [Learn more.](#)

Form elements have associated labels

Labels ensure that form controls are announced properly by assistive technologies, such as screen readers. [Learn more.](#)

Links have a discernible name

Link text (and alternative text for images, when used as links) that is discernible, unique and focusable improves the navigation experience for screen reader users. [Learn more.](#)

Lists contain only `` elements and script supporting elements (`<script>` and `<template>`).

Screen readers have a specific way of announcing lists. Ensuring proper list structure aids screen reader output. [Learn more.](#)

List items (``) are contained within `` or `` parent elements

Screen readers require list items (``) to be contained within a parent `` or `` to be announced properly. [Learn more.](#)

`[user-scalable="no"]` is not used in the `<meta name="viewport">` element and the `[maximum-scale]` attribute is not less than 5.

Disabling zooming is problematic for users with low vision who rely on screen magnification to properly see the contents of a web page. [Learn more.](#)

Not applicable (26)

`[accesskey]` values are unique

Access keys let users quickly focus a part of the page. For proper navigation, each access key must be unique. [Learn more.](#)

`button`, `link`, and `menuitem` elements have accessible names

When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more.](#)

`[aria-hidden="true"]` elements do not contain focusable descendents

Focusable descendents within an `[aria-hidden="true"]` element prevent those interactive elements from being available to users of assistive technologies like screen readers. [Learn more.](#)

ARIA input fields have accessible names

When an input field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more.](#)

ARIA `meter` elements have accessible names

When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more.](#)

ARIA `progressbar` elements have accessible names

When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more.](#)

`[role]`s have all required `[aria-*)` attributes

Some ARIA roles have required attributes that describe the state of the element to screen readers. [Learn more.](#)

Elements with an ARIA `[role]` that require children to contain a specific `[role]` have all required children.

Some ARIA parent roles must contain specific child roles to perform their intended accessibility functions. [Learn more.](#)

`[role]`s are contained by their required parent element

Some ARIA child roles must be contained by specific parent roles to properly perform their intended accessibility functions. [Learn more.](#)

`[role]` values are valid

ARIA roles must have valid values in order to perform their intended accessibility functions. [Learn more.](#)

ARIA toggle fields have accessible names

When a toggle field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more.](#)

ARIA `tooltip` elements have accessible names

When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more.](#)

ARIA `treeitem` elements have accessible names

When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more.](#)

`<dl>`'s contain only properly-ordered `<dt>` and `<dd>` groups, `<script>`, `<template>` or `<div>` elements.

When definition lists are not properly marked up, screen readers may produce confusing or inaccurate output. [Learn more.](#)

Definition list items are wrapped in `<dl>` elements

Definition list items (`<dt>` and `<dd>`) must be wrapped in a parent `<dl>` element to ensure that screen readers can properly announce them. [Learn more.](#)

`[id]` attributes on active, focusable elements are unique

All focusable elements must have a unique `id` to ensure that they're visible to assistive technologies. [Learn more.](#)

No form fields have multiple labels

Form fields with multiple labels can be confusingly announced by assistive technologies, like screen readers, which use either the first, the last or all of the labels. [Learn more.](#)

`<frame>` or `<iframe>` elements have a title

Screen reader users rely on frame titles to describe the contents of frames. [Learn more.](#)

`<input type="image">` elements have `[alt]` text

When an image is being used as an `<input>` button, providing alternative text can help screen reader users understand the purpose of the button. [Learn more.](#)

The document does not use `<meta http-equiv="refresh">`

Users do not expect a page to refresh automatically, and doing so will move focus back to the top of the page. This may create a frustrating or confusing experience. [Learn more.](#)

`<object>` elements have `[alt]` text

Screen readers cannot translate non-text content. Adding alt text to `<object>` elements helps screen readers convey meaning to users. [Learn more.](#)

No element has a `[tabindex]` value greater than 0

A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. [Learn more.](#)

Cells in a `<table>` element that use the `[headers]` attribute refer to table cells within the same table.

Screen readers have features to make navigating tables easier. Ensuring `<td>` cells using the `[headers]` attribute only refer to other cells in the same table may improve the experience for screen reader users. [Learn more.](#)

`<th>` elements and elements with `[role="columnheader"/"rowheader"]` have data cells they describe. ^

Screen readers have features to make navigating tables easier. Ensuring that table headers always refer to some set of cells may improve the experience for screen reader users. [Learn more](#).

`[lang]` attributes have a valid value ^

Specifying a valid [BCP 47 language](#) on elements helps ensure that text is pronounced correctly by a screen reader. [Learn more](#).

`<video>` elements contain a `<track>` element with `[kind="captions"]` ^

When a video provides a caption it is easier for deaf and hearing-impaired users to access its information. [Learn more](#).



Best Practices

Passed audits (17) ^

Uses HTTPS ^

All sites should be protected with HTTPS, even ones that don't handle sensitive data. This includes avoiding [mixed content](#), where some resources are loaded over HTTP despite the initial request being served over HTTPS. HTTPS prevents intruders from tampering with or passively listening in on the communications between your app and your users, and is a prerequisite for HTTP/2 and many new web platform APIs. [Learn more](#).

Links to cross-origin destinations are safe ^

Add ``rel="noopener"`` or ``rel="noreferrer"`` to any external links to improve performance and prevent security vulnerabilities. [Learn more](#).

Avoids requesting the geolocation permission on page load ^

Users are mistrustful of or confused by sites that request their location without context. Consider tying the request to a user action instead. [Learn more](#).

Avoids requesting the notification permission on page load ^

Users are mistrustful of or confused by sites that request to send notifications without context. Consider tying the request to user gestures instead. [Learn more](#).

Avoids front-end JavaScript libraries with known security vulnerabilities ^

Some third-party scripts may contain known security vulnerabilities that are easily identified and exploited by attackers. [Learn more](#).

Allows users to paste into password fields ^

Preventing password pasting undermines good security policy. [Learn more](#).

Displays images with correct aspect ratio ^

Image display dimensions should match natural aspect ratio. [Learn more.](#)

Serves images with appropriate resolution

Image natural dimensions should be proportional to the display size and the pixel ratio to maximise image clarity. [Learn more.](#)

Page has the HTML doctype

Specifying a DOCTYPE prevents the browser from switching to quirks mode. [Learn more.](#)

Properly defines charset

A character encoding declaration is required. It can be done with a `<meta>` tag in the first 1,024 bytes of the HTML or in the Content-Type HTTP response header. [Learn more.](#)

Avoids `unload` event listeners

The `unload` event does not fire reliably and listening for it can prevent browser optimisations like the back-forward cache. Consider using the `pagehide` or `visibilitychange` events instead. [Learn More](#)

Avoids application cache

Application cache is deprecated. [Learn more.](#)

Detected JavaScript libraries

All front-end JavaScript libraries detected on the page. [Learn more.](#)

Name	Version
Bootstrap	4.5.2
jQuery	3.6.0

Avoids deprecated APIs

Deprecated APIs will eventually be removed from the browser. [Learn more.](#)

No browser errors logged to the console

Errors logged to the console indicate unresolved problems. They can come from network request failures and other browser concerns. [Learn more](#)

Page has valid source maps

Source maps translate minified code to the original source code. This helps developers to debug in production. In addition, Lighthouse is able to provide further insights. Consider deploying source maps to take advantage of these benefits. [Learn more.](#)

☒ Show 3rd-party resources (2)

URL	Map URL
...js/bootstrap.min.js (stackpath.bootstrapcdn.com)	...js/bootstrap.min.js.map (stackpath.bootstrapcdn.com)
...umd/popper.min.js (cdnjs.cloudflare.com)	...umd/popper.min.js.map (cdnjs.cloudflare.com)

No issues in the [Issues](#) panel in Chrome Devtools

Issues logged to the `Issues` panel in Chrome Devtools indicate unresolved problems. They can come from network request failures, insufficient security controls, and other browser concerns. Open up the Issues panel in Chrome DevTools for more details on each issue.

Not applicable (1) ^

Fonts with `font-display: optional` are preloaded ^

Preload `optional` fonts so that first-time visitors may use them. [Learn more](#)



SEO

These checks ensure that your page is optimised for search engine results ranking. There are additional factors that Lighthouse does not check that may affect your search ranking. [Learn more](#).

Additional items to manually check (1) — Run these additional validators on your site to check additional SEO best practices. ^

Structured data is valid ^

Run the [Structured Data Testing Tool](#) and the [Structured Data Linter](#) to validate structured data. [Learn more](#).

Passed audits (13) ^

Has a `<meta name="viewport">` tag with `width` or `initial-scale` ^

Add a `<meta name="viewport">` tag to optimise your app for mobile screens. [Learn more](#).

Document has a `<title>` element ^

The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. [Learn more](#).

Document has a meta description ^

Meta descriptions may be included in search results to concisely summarise page content. [Learn more](#).

Page has successful HTTP status code ^

Pages with unsuccessful HTTP status codes may not be indexed properly. [Learn more](#).

Links have descriptive text ^

Descriptive link text helps search engines understand your content. [Learn more](#).

Links are crawlable ^

Search engines may use `href` attributes on links to crawl websites. Ensure that the `href` attribute of anchor elements links to an appropriate destination, so that more pages of the site can be discovered. [Learn more](#)

Page isn't blocked from indexing ^

Search engines are unable to include your pages in search results if they don't have permission to crawl them. [Learn more](#).

robots.txt is valid ^

If your robots.txt file is malformed, crawlers may not be able to understand how you want your website to be crawled or indexed. [Learn more](#).

Image elements have [alt] attributes ^

Informative elements should aim for short, descriptive alternative text. Decorative elements can be ignored with an empty alt attribute. [Learn more](#).

Document has a valid hreflang ^

hreflang links tell search engines what version of a page they should list in search results for a given language or region. [Learn more](#).

Document uses legible font sizes — 100% legible text ^

Font sizes less than 12px are too small to be legible and require mobile visitors to 'pinch to zoom' in order to read. Strive to have >60% of page text ≥ 12 px. [Learn more](#).

☐ Show 3rd-party resources (0)

Source	Selector	% of page text	Font size
Legible text		100.00%	≥ 12 px

Document avoids plugins ^

Search engines can't index plug-in content, and many devices restrict plug-ins or don't support them. [Learn more](#).

Tap targets are sized appropriately — 100% appropriately sized tap targets ^

Interactive elements such as buttons and links should be large enough (48 x 48px) and have enough space around them to be easy enough to tap without overlapping onto other elements. [Learn more](#).

Not applicable (1) ^

Document has a valid rel=canonical ^

Canonical links suggest which URL to show in search results. [Learn more](#).



progressive web app

These checks validate the aspects of a progressive web app. [Learn more](#).

Installable**▲ Web app manifest does not meet the installability requirements — 1 reason** ^

Browsers can proactively prompt users to add your app to their home screen, which can lead to higher engagement. [Learn more](#).

Failure reason

No manifest was fetched

PWA Optimised**▲ Does not register a service worker that controls page and `start_url`** ^

The service worker is the technology that enables your app to use many progressive web app features, such as offline, add to home screen and push notifications. [Learn more](#).

Redirects HTTP traffic to HTTPS ^

If you've already set up HTTPS, make sure that you redirect all HTTP traffic to HTTPS in order to enable secure web features for all your users. [Learn more](#).

▲ Is not configured for a custom splash screen Failures: No manifest was fetched. ^

A themed splash screen ensures a high-quality experience when users launch your app from their home screens. [Learn more](#).

▲ Does not set a theme colour for the address bar. Failures: No manifest was fetched, No `<meta name="theme-color">` tag found. ^

The browser address bar can be themed to match your site. [Learn more](#).

Content is sized correctly for the viewport ^

If the width of your app's content doesn't match the width of the viewport, your app might not be optimised for mobile screens. [Learn more](#).

Has a `<meta name="viewport">` tag with `width` or `initial-scale` ^

Add a `<meta name="viewport">` tag to optimise your app for mobile screens. [Learn more](#).

▲ Does not provide a valid `apple-touch-icon` ^

For ideal appearance on iOS when users add a progressive web app to the home screen, define an `apple-touch-icon`. It must point to a non-transparent 192px (or 180px) square PNG. [Learn More](#).

▲ Manifest doesn't have a maskable icon No manifest was fetched ^

A maskable icon ensures that the image fills the entire shape without being letterboxed when installing the app on a device. [Learn more](#).

Additional items to manually check (3) — These checks are required by the baseline [PWA checklist](#) but are not automatically checked by Lighthouse. They do not affect your score but it's important that you verify them manually.

Site works cross-browser ^

To reach the most users, sites should work across every major browser. [Learn more.](#)

Page transitions don't feel like they block on the network ^

Transitions should feel snappy as you tap around, even on a slow network. This experience is key to a user's perception of performance. [Learn more.](#)

Each page has a URL ^

Ensure individual pages are deep linkable via URL and that URLs are unique for the purpose of shareability on social media. [Learn more.](#)

Runtime settings

URL	https://landingpage.saltcorn.com/
Fetch time	20 Apr 2021, 19:48 BST
Device	Emulated Moto G4
Network throttling	150 ms TCP RTT, 1,638.4 Kbps throughput (Simulated)
CPU throttling	4x slowdown (Simulated)
Channel	devtools
User agent (host)	Mozilla/5.0 (Macintosh; Intel Mac OS X 11_2_3) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/89.0.4389.128 Safari/537.36
User agent (network)	Mozilla/5.0 (Linux; Android 7.0; Moto G (4)) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/84.0.4143.7 Mobile Safari/537.36 Chrome-Lighthouse
CPU/Memory power	2610
Axe version	4.1.1

Generated by **Lighthouse** 7.0.0 | [File an issue](#)